



# 6-in-1 Multi-band Antenna

## MODEL: AU-4C

Multi-band antenna for any telemetry applications



©2008 San Jose Technology, Inc. All specifications subject to change without notice.

The **AU-4C** is the multi-band antenna, which covers GPS/850/900/1800/1900 /2100 MHz frequencies. It is specially designed for any telemetry applications, which utilize those bands. The high sensitivity of **AU-4C** will enhance the performance of your telemetry devices.

### Features:

1. Low profile structure without a whip
2. Both permanent and magnetic mountings are available
3. IPX7 fully waterproof

### Applications:

1. Vehicle tracking
2. Asset tracking
3. GPS Navigation
4. Telemetry Application

### Specification:

Category	GPS Antenna	Communication Antenna
Frequency	1.57542GHz (L1 BAND)	824 MHz~894 MHz (GSM 850MHz) 890~960 MHz (GSM 900MHz) 1710~1890 MHz (DCS 1800MHz) 1850~1990 MHz (PCS 1900MHz) 1920~2170 MHz (WCDMA 2100MHz)
Gain	27dB	1 dBi
V.S.W.R	≤ 1.8.	≤ 2.0 (with 5m cable)
Noise Figure	2.0 Max	-
Band Width	10 MHz	136MHz for 824MHz~960MHz 280MHz for 1710MHz~1990MHz 250MHz for 1920MHz~2170MHz
Impedance	50 Ohm	50 Ohm
Cable/Connector	3 Meter-RG174/ SMA	3 Meter-RG174/SMA
Polarization	R.H.C.P	Linear
Power supply	3.0 ~ 5.5V DC	-
Power Consumption	12mA	-
Power Handling Capacity	-	10W
Dimension	63mm(Dia.) x 15.6mm(H)	
Operation Temperature	-40°C to +80°C	
Storage Temperature	-45°C to +100°C	

\* This specification is subject to change without prior notice

Data Updated: Aug 01, 2007

©2008 San Jose Technology, Inc.  
All specifications subject to change without notice.