



# 6-in-1 Multi-band Antenna

## MODEL: AW-4S

Multi-band antenna for any telemetry applications



©2008 San Jose Technology, Inc. All specifications subject to change without notice.

The **AW-4S** is the multi-band antenna that covers GPS/850/900/1800/1900/2400 MHz frequencies. It is specially designed for any telemetry applications, which utilize those bands. The high sensitivity of **AW-4S** will enhance the performance of your telemetry devices.

### Features:

1. Low profile structure without a whip
2. Both permanent and magnetic mountings are available
3. Covers all the mobile communication network
4. Fully waterproof
5. Wifi frequency embedded

### Applications:

1. Vehicle tracking
2. Asset tracking
3. GPS Navigation
4. Telemetry Application

**Specification:**

Category	GPS Antenna	Communication Antenna
Frequency	1.57542GHz (L1 BAND)	824 MHz ~ 894 MHz (GSM 850MHz) 890~960 MHz (GSM 900MHz) 1710~1890 MHz (DCS 1800MHz) 1850 ~ 1990 MHz (PCS 1900MHz) 2400 ~ 2483 MHz (Wifi 2400MHz)
Gain	27dB	850 MHz = 1.0 dBi 900 MHz = 1.0 dBi 1800 MHz = 1 dBi 1900 MHz = 1 dBi 2400 MHz = 0 dBi
V.S.W.R	≤ 1.8.	≤ 2.0 (with 5m cable)
Noise Figure	2.0 Max	-
Band Width	2 MHz	136MHz for frequency of 824MHz-960MHz 280MHz for frequency of 1710MHz-1990MHz 83 MHz for frequency of 2400-2483MHz
Impedance	50 Ohm	50 Ohm
Cable/Connector	5 Meter-RG174/ SMA	5 Meter-RG174/SMA
Polarization	R.H.C.P	Linear
Power supply	3.0 ~ 5.5V DC	-
Power Consumption	12mA	-
Power Handling Capacity	-	10W
Dimension	63mm(Dia.) x 15.6mm(H)	
Operation Temperature	-40°C to +80°C	
Storage Temperature	-45°C to +100°C	

©2008 San Jose Technology, Inc.  
All specifications subject to change without notice.

\* This specification is subject to change without prior notice **Data Updated:** Aug 01, 2007